

PG PLUS FID STATION H2 + ZERO AIR GENERATOR

DETECTOR GRADE



North America & South America contact:

Europe, Asia, Africa, & Australia/Oceania contact:

VICI DBS USA

tel: +1 713-263-6970
fax: +1 713-263-6971
web: www.vicidbs.com

VICI AG INTERNATIONAL

tel: +41 41 925-6200
fax: +41 41 925-6201
web: www.vicidbs.com

DESCRIPTION

The VICI DBS® PG Plus FID Station is a unique instrument that combines the reliability of the hydrogen generator with a zero air generator into one compact package. The FID Station can be installed under the GC taking no additional bench space. This simple but effective instrument can supply all your FID gas requirements. Designed as a hazard free alternative to high pressure cylinders, all that is required is deionized water, compressed air and a standard electrical supply for weeks of continuous operation.


Innovative software control allows unrivaled operational performance and safety as well as the additional options of auto water feed, remote networking and cascading for built in redundancy. With a maximum output capacity of 250 mL/min, one generator can supply up to 6 GC detectors. The compact design allows the generator to be installed directly in the laboratory eliminating the requirement for long gas lines and guaranteeing the delivery of high purity gas to your GC.

A sophisticated control system connected to an easy to use touch screen control continuously monitors vital operating parameters to ensure a safe and consistent performance. Built in sensors will shut the generator down if internal/external leaks are present, contaminated water, low water or over pressure. This is why VICI DBS generators meet the strict safety guidelines to be certified for CE, FCC, and MET (UL and CSA compliant).



INCREASE EFFICIENCY

A constant gas supply with a guaranteed purity, eliminates interruptions of analyses to change cylinders and reduces the amount of instrument re-calibrations required.



ENHANCE PERFORMANCE

Gas generators can be installed in the laboratory close to the instrument, eliminating the need for long gas lines from external cylinder supplies. A constant guaranteed high purity gas supply improves stability and ensures greater reproducibility of results.




IMPROVE SAFETY

Gas is produced on demand, which allows for the safe use of the hydrogen generator when cylinders are prohibited or regarded as potentially dangerous. Sophisticated software control and full alarm capability, including for hydrogen leaks, gives the users full control of the gas supply.

OPERATING DIAGRAM

Hydrogen is produced from the hydrolysis of deionized water across a PEM (proton exchange membrane), housed in a 100% titanium cell. The output hydrogen is dried via a dual stage process, a gas liquid separator and a unique dual high performance membrane dryer. In addition to water all that the generator requires is a standard connection and supply of electricity for a continuous 24/7 supply of high purity hydrogen. Consumable items are limited to the replacement of a deionizer bag every six months.





FEATURES

Produces a continuous supply of hydrogen & zero air | Compact and robust design to accommodate up to 80 kg (176 lbs) top loading - suits all GC manufacturers | On-demand supply 24/7 | H2 Flow rate: 100 to 250 mL/min & zero air up to 5 L/min | H2 Purity: >99.9996% & zero air purity, 0.1 ppm of hydrocarbons | Pressure: 11 barg (160 psig) | Proprietary 100% titanium cell technology | Unique permeation membrane drying system | USB connectivity | 2-year complete cell and product warranty | Easy to install, operate and maintain



BENEFITS

Eliminates dangerous high pressure cylinders helping to keep your employees safer | Frees up valuable bench space | Removes the logistics, inconvenience, downtime and costs of a cylinder system | Flow capacity and purity to match your specific instrument demands | Ideal for all GC detector applications | Exceeds the requirements for the most demanding GC applications | Superior hydrogen production with reliable long life cell | Minimal maintenance - low cost of ownership | PC Monitoring for maintenance, diagnostics and remote connection | Peace of mind | Improve your laboratory work flow and productivity



OPTIONS

Zero air option 1.8 L/min or 5 L/min | I/O board | Remote control software (RS232 or USB) | Cascading hardware (standard or high purity) | FID-station MS extension | Automatic water refill



APPLICATIONS

GC APPLICATIONS

- GC-FID fuel gas
- GC-NPD plasma gas
- GC-FPD fuel gas

ANALYZER APPLICATIONS

- Total Hydrocarbon Analyzer (THA) fuel gas

OTHER APPLICATIONS

- Hydrogenation reactors
- Hydrogen fuel cells

ORDERING INFORMATION (for best service, please call to discuss your application before placing your order).

PG PLUS 100 FID STATION

DB-FHG100-EU	230-240V/50-60Hz
DB-FHG100-US	115V/60Hz
DB-FHG100-JP	100V/60Hz

PG PLUS 250 FID STATION

DB-FHG250-EU	230-240V/50-60Hz
DB-FHG250-US	115V/60Hz
DB-FHG250-JP	100V/60Hz

MODELS & SPECS	PG PLUS 100 FID STATION	PG PLUS 250 FID STATION
Flow mL/min	100	250
Purity	>99.9996%	
Dewpoint at 7 barg (100 psig)	-25°C (-13°F)	
Outlet pressure barg (psig)	0.5 to 11 (7 to 160)	
Technology	PEM (proton exchange membrane) - 100% titanium cell	
Drying system	Regenerative permeation membrane	
Deionised water quality	Minimum <1 micro S/cm @ 25°C - 1 Mohm-cm @ 25°C - ASTM II Recommended <0.2 microS/cm @ 25°C - 5 Mohm-cm @ 25°C - ASTM II	
Internal water tank (liters)	7	
Safety	Automatic shut down - internal/external hydrogen leak, overpressure and low water	
Display	Touch screen with operating parameters, system status and safety alarms	
LED Indicators	Power on/off, system ready, errors	
Interface	USB mod A	
Load capacity kg (lbs)	80 (176)	
Electrical supply	110-120V 60Hz / 220-240V 50Hz	
Power consumption (watts)	65	115
Dimensions mm (in)	690W x 150H x 680D (27W x 6H x 26.7D)	
Weight kg (lbs)	39 (86)	
Shipping dimensions mm (in)	890W x 385H x 800D (35W x 15.1H x 31.4D)	
Shipping weight kg (lbs)	45 (99)	
Operating temp °C (°F)	15 to 35 (59 to 95)	
Outlet connection	1/8" Compression	
Certification	CE, FCC, and MET (UL and CSA compliant)	

CHOOSE YOUR ZERO AIR FLOW RATE

Zero Air is built into the PG Plus FID Station and you have two choices for flow rates. When ordering, be sure to select the Zero Air flow rate best suited to your needs.

ZERO AIR FLOW OPTIONS	DB-FH-1800	DB-FH-5000
Flow mL/min	1800	5000
Purity - hydrocarbons + CO	<0.1 ppm	
Inlet pressure barg (psig)	4.5 to 10 (65 to 145)	
Inlet air quality	Clean dry compressed air ISO8573-1:2010 Class 1.2.1	
Max outlet pressure barg (psig)	5 (73)	
Max HC in	100 ppm	
Max CO in	50 ppm	